

NORTHWEST CORNER SECTION 06, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ON PAGE 101 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 33" X 15" X 5"** FOR THE CLOSING CORNER TO RANGES 12 & 13 EAST IN THE NORTH BOUNDARY OF TOWNSHIP 21 SOUTH, 26.59 CHAINS WEST OF THE CORNER TO RANGES 12 & 13 EAST IN THE SOUTH BOUNDARY OF TOWNSHIP 20 SOUTH ON JUNE 2, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 45.12 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 26" X 12" X 2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-21-13
 - 2) 85.12 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-21-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 16 DATED MARCH 1-5, 1870 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 6-21-13, SAID THAT **HE FOUND THE STONE** AT THE CORNER TO RANGES 12 & 13 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 68 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 216 DATED OCTOBER 3, 1872 TO ESTABLISH THE CENTER CORNER OF SECTION 36-20-12 AND SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 32 INTO QUARTERS, SAID THAT **HE FOUND THE STONE** AT THE CORNER BETWEEN SECTION 1-21-12 AND 6-21-13 AT THE TOWNSHIP CORNER AND ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 986' WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 36-20-12
 - 2) 336' EAST ON THE 4TH STANDARD PARALLEL TO THE POST HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 36-20-12
 - 3) 1,658' EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-20-12
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 57 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 114 DATED JANUARY 14, 1875 TO ESTABLISH THE 1/4 CORNER ON THE EAST BOUNDARY AND THE CENTER CORNER OF SECTION 1-21-12, SAID THAT **HE FOUND THE STONE** AT THE CORNER OF TOWNSHIP 21, RANGES 12 & 13 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 888' WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 36-20-12
 - 2) 2,640' WEST ON THE 4TH STANDARD PARALLEL TO THE POST HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 1-21-12
 - 3) 3002' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 1-21-12
 - 4) 5,642' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-21-12
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 13, 2005, FOR PROJECT NUMBER 05129-02, SURVEY F01002 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR A SURVEY TO MARK THE EXTERIOR OF SECTION 1-21-12 FOR JOHN BECHTEL, SAID THAT HE

DEEMED THAT THE NORTHEAST CORNER OF SECTION 1-21-12 ON THE 4TH STANDARD PARALLEL WAS **LOST** AS IT FALLS IN A DRAINAGE DITCH. HE RESET THIS CORNER BY THE RETRACEMENT AND PRORATION OF A PERMANENT SURVEY BY ROBERT MILLIKEN IN 1875 RECORDED IN SURVEY BOOK "C" ON PAGE 114. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP AS A WITNESS CORNER AT 30.00 FEET SOUTH OF THE TRUE POSITION** OF THE NORTHEAST CORNER OF SECTION 1-21-12 AT THE TOWNSHIP CORNER.

- 1) **30.00' NORTH TO THE TRUE POSITION FOR THE SECTION CORNER**
- 2) 6.95' NE TO A 40 D NAIL & WASHER IN THE COUTH FACE OF AN 8" HACKBERRY TREE
- 3) 15.7' WEST TO A 40 D NAIL & WASHER IN THE NORTH SIDE OF A 16" ELM TREE
- 4) 2.5' SOUTH TO A 40 D NAIL & WASHER IN THE WEST SIDE OF AN 8" ELM TREE
- 5) 30.0' WEST TO A CROP LINE - EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES FROM THE TRUE POSITION:

- 1) 1,764.23' EAST ON THE 4TH STANDARD PARALLEL TO THE GLO STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-20-12
- 2) 2,993.46' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 1-21-12
- 3) 5,625.96' SOUTH ON TH RANGE LINE TO THE BENT 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-21-12
- 4) 10,922.83' SOUTH ON THE RANGE LINE TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-21-12
- 5) 886.00' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-20-12
- 6) 2,660.00' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 1-21-12
- 7) 3,526.23' WEST ON THE 4TH STANDARD PARALLEL TO PARKMAN'S PERMANENT SURVEY STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-20-12

NORTHWEST CORNER 06-21-13