

**WEST 1/4 CORNER SECTION 06, TOWNSHIP 21 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 101 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 26" X 12" X 2"** FOR THE WEST 1/4 CORNER OF SECTION 6-21-13 ON THE WEST TOWNSHIP BOUNDARY ON JUNE 2, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 45.12 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 33" X 15" X 5" LIMESTONE THEY SET FOR THE CLOSING CORNER TO TOWNSHIP 21 SOUTH, RANGES 12 & 13 EAST
- 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-21-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 57 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 114 DATED JANUARY 14, 1875 TO ESTABLISH THE 1/4 CORNER ON THE EAST BOUNDARY AND THE CENTER CORNER OF SECTION 1-21-12, SAID THAT **HE SET A 15" X 8" X 3" STONE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 1-21-12 ON THE RANGE LINE BETWEEN THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-21-12 AND THE CORNER TO TOWNSHIP 21, RANGES 12 & 13 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-21-12
- 2) 3002' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE CORNER TO TOWNSHIP 21, RANGES 12 & 13
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 13, 2005, FOR PROJECT NUMBER 05129-02, SURVEY F01002 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR THE SURVEY OF THE SOUTHEAST QUARTER OF SECTION 1-21-12 FOR JOHN BECHTEL, SAID THAT HE DEEMED THAT THE EAST 1/4 CORNER OF SECTION 1-21-12 ON THE RANGE LINE WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 1-21-12 BY THE RETRACEMENT AND PRORATION OF A PERMANENT SURVEY BY ROBERT MILLIKEN IN 1875 RECORDED IN SURVEY BOOK "C" ON PAGE 114, AND ON LINE BETWEEN THE SOUTHEAST CORNER AND NORTHEAST CORNER OF SECTION 1-21-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL. HE SAID IN HIS *REPORT OF SURVEY* THE STONE THAT WAS SET BY MILLIKEN WAS **NOT** FOUND AS THE POSITION WAS FOUND TO FALL IN AN EXISTING STREAM BED OR DITCH, AND THE POSITION WAS DETERMINED TO BE ON LINE BETWEEN THE NORTHEAST AND SOUTHEAST CORNERS OF SECTION 1-21-12 AND AT THE PRORATION OF MILLIKEN'S CHAIN FOR THIS LINE.
- 1) 13.8' NNE TO A 40 D SPIKE & WASHER IN THE WEST SIDE OF A 22" HACKBERRY
- 2) 12.7' ESE TO A 40 D SPIKE & WASHER IN THE SOUTH SIDE OF A 24" ELM TREE
- 3) 15.1' NW TO A 40 D SPIKE & WASHER IN THE EAST ROOT OF A 24" HACKBERRY
- 4) IN THE CENTER OF A NORTH-SOUTH DRAIN
- 5) 4.0' NORTH TO A DRAIN FROM THE WEST
- 6) 12.0' SOUTH TO A LINE HEDGE EXTENDED WEST
- 7) 12.0' WEST TO A LINE HEDGE EXTENDED SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,993.46' NORTH ON THE RANGE LINE TO THE TRUE LOCATION FOR THE NORTHEAST CORNER OF SECTION 1-21-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL, AS WITNESSED BY THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET AT **30.00' SOUTH DUE TO A CREEK** [MILLIKEN = 3,002']

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,633.50' SOUTH ON THE RANGE LINE TO THE BENT 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-21-12 [MILLIKEN = 2,640']
- 3) 7,929.37' SOUTH ON THE RANGE LINE TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-21-12

WEST QUARTER CORNER 06-21-13