

**NORTH 1/4 CORNER SECTION 07, TOWNSHIP 21 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 699 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-21-13.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 30.37 CHAINS WEST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-21-13 ON THE WEST TOWNSHIP BOUNDARY
  - 2) 40.00 CHAINS EAST TO THE 24" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-21-13
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 16, A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 16 DATED MARCH 1-5, 1870 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 6-21-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 6-21-13 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,640' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 6-21-13
  
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 146 DATED APRIL 8, 1876, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 6-21-13 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 5,695' NORTH TO THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 6-21-13 ON THE 4<sup>TH</sup> STANDARD PARALLEL
  
- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 10, 1986, FOR JOB NUMBER 86134, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 6-21-13 WAS **OBLITERATED**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 6-21-13.
  - 1) 44.0' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 2) 69.9' NNW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 3) IN LINE WITH A FENCE TO THE SOUTH EXTENDED
  - 4) 36.0' NORTH AND SOUTH TO AN EAST FENCE LINE
  
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 28, 2006 FOR PROJECT NUMBER 06104-02, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A TRACT IN THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-21-13 AND A TRACT IN FRACTIONAL SECTION 7-21-13 FOR KENT GREIDER, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTH 1/4 CORNER OF FRACTIONAL SECTION 7-21-13 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE IN 1986.
  - 1) 45.8' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 2) 69.6' NNW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 3) IN LINE WITH A FENCE TO THE SOUTH EXTENDED
  - 4) 36.4' SOUTH TO A CONCRETE NAIL & WASHER IN A CORNER POST
  - 5) 26.0' NORTH TO A FENCE TO THE EAST EXTENDEDHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,024.51' WEST TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF FRACTIONAL SECTION 7-21-13 ON THE RANGE LINE [AKA NORTHWEST CORNER OF GOVERNMENT LOT 1]
  - 2) 2,623.76' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF FRACTIONAL SECTION 7-21-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,643.59' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF FRACTIONAL SECTION 7-21-13
- 4) 5,282.33' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF FRACTIONAL SECTION 7-21-13
- 5) 2,640.00' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF FRACTIONAL SECTION 6-21-13
- 6) 5,674.95' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF FRACTIONAL SECTION 6-21-13 ON THE 4<sup>TH</sup> STANDARD PARALLEL

NORTH QUARTER CORNER 07-21-13