

NORTHWEST CORNER SECTION 10, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ON PAGE 689 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 12" X 3"** FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-21-13.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 25" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-21-13
 - 2) 87.81 CHAINS NORTH TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-21-13 ON THE 4TH STANDARD PARALLEL
 - 3) 40.23 CHAINS EAST TO THE 28" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-21-13
 - 4) 80.45 CHAINS EAST TO THE 27" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-13 ON THE COUNTY LINE

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 219 [PACKET 279 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY DANIEL RICH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-13 AND 21-13 THAT HE SURVEYED ON AUGUST 14 & 15, 1874, THAT WAS FILED ON FEBRUARY 5, 1875 AS A 50 FOOT WIDE ROAD EXCEPT AT THE CROSSING OF EAGLE CREEK IN SECTION 33-20-13 WHERE IT IS TO BE 60 FEET WIDE FOR 10 RODS ON EACH SIDE OF THE CENTER OF THE CHANNEL OF THE CREEK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-21-13 ON THIS ROAD SURVEY
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 3-21-13 ON THE 4TH STANDARD PARALLEL AT A TURN TO THE WEST
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO AN ANGLE AT 38.66 RODS SOUTH OF THE NORTHWEST CORNER OF SECTION 15-21-13 AT A TURN TO THE SOUTHWESTERLY DUE TO A CREEK

- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 129 DATED APRIL 27, 1882 TO SUBDIVIDE SECTION 4-21-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 4-21-13 ON THIS SURVEY.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 19.88 CHAINS WEST TO THE STONE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 4-21-13
 - 2) 39.76 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-21-13

- 4) IN A FIELD BOOK LABELED "NUMBER 39 PRELIMINARY NOTES F.A.S. ROUTE NUMBER 1122" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE NUMBER 8 IT SHOWS A **5/8" REBAR AT P. I. STATION 522+73.9** AT THE NORTHWEST CORNER OF SECTION 10-21-13.
 - 1) 35.5' NE TO THE NORTHWEST CORNER OF A CULVERT HEADWALL
 - 2) 36.5' NW TO THE NORTHEAST CORNER OF A CULVERT HEADWALL

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 28, 2005, FOR PROJECT NUMBER 05392-02, SURVEY F03002 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A SURVEY OF THE SOUTH LINE OF THE NORTHWEST FRACTIONAL QUARTER OF SECTION 3-21-13 FOR ALMA JEAN MAUTZ, SAID THAT **HE FOUND A 1/2" REBAR AT 24" DEEP** AT THE SOUTHWEST CORNER OF SECTION 3-21-13. **HE SET A 5/8" X 24" REBAR WITH A**

LYON COUNTY CAP OVER THE 1/2" REBAR THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-21-13.

- 1) 50.55' SE TO A 40 D NAIL & SHINER IN THE TOP OF A CORNER FENCE POST
- 2) 41.00' SW TO A 40 D NAIL & SHINER IN A POWER POLE
- 3) 33.80' NW TO A 40 D NAIL & SHINER IN A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,649.47' NORTH [40.0 CHAINS GLO] TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 3-21-13
- 2) 5,816.25' NORTH [87.81 CHAINS GLO] TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 3-21-13 ON THE 4TH STANDARD PARALLEL

6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 13, 2009 FOR PROJECT NUMBER 09096-02, SURVEY F03003 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A SURVEY OF THE EAST LINE OF THE WEST HALF OF THE SOUTHWEST QUARTER OF SECTION 3-21-13 FOR APAC, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTHWEST CORNER OF SECTION 3-21-13 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED NOVEMBER 2005.

- 1) 49.95' SE TO A CONCRETE NAIL & BOTTLE CAP IN THE WEST FACE OF A CORNER FENCE POST
- 2) 41.0' SW TO A CONCRETE NAIL & BOTTLE CAP IN THE SOUTH FACE OF A POWER POLE
- 3) 34.3' NW TO A CONCRETE NAIL & BOTTLE CAP IN THE NORTH FACE OF A POWER POLE
- 4) 1' SOUTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 60 EAST-WEST
- 5) 2' EAST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD "Y" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,649.50' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY HE FOUND AT THE NORTHWEST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 3-21-13
- 2) 1,331.96' EAST TO THE 3" X 3" X 18" LIMESTONE HE FOUND WITH THE BOTTOM FIRM IN BROWN DIRT LAYED DOWN TO THE WEST AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 3-21-13. **HE REPLACED THE STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP AND THIS 5/8" REBAR WAS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 40.00' NORTH**

NORTHWEST CORNER 10-21-13