

**NORTHWEST CORNER SECTION 19, TOWNSHIP 21 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 100 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 10" X 3"** FOR THE CORNER TO SECTIONS 18 & 19-21-13 ON THE WEST TOWNSHIP BOUNDARY ON JUNE 2, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 19-21-13
- 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 15" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-21-13
- 3) 30.90 CHAINS EAST TO THE 30" X 15" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-21-13
- 4) 70.90 CHAINS EAST TO THE 25" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-21-13

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 61, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 61 DATED SEPTEMBER 5, 1884 AT THE REQUEST OF J. W. ELLIS FOR A ROAD IN TOWNSHIP 21, RANGES 12 & 13, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-21-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 12-21-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 25-21-12; THEN CONTINUES SOUTH ON THE RANGE LINE AT 45 FEET WIDE CENTERING THE WEST LINE AT 30 FEET WEST OF THE SECTION LINE, WHICH GIVES BUT 15 FEET ON THE EAST SIDE, FOR 880 FEET; THEN CONTINUES SOUTH ON THE RANGE LINE AT 50 FEET WIDE, 30 FEET ON THE WEST SIDE AND 20 FEET ON THE EAST SIDE, FOR 1,760 FEET TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-21-12; THEN CONTINUES SOUTH ON THE RANGE LINE AT 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 36-21-12 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE TO BEGIN THIS ROAD SURVEY

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 280 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 70 TO 72 PETITIONED BY J. W. ELLIS AND OTHERS FOR A COUNTY ROAD ON THE RANGE LINE BETWEEN TOWNSHIPS 21-12 AND 21-13 [PACKET 556 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD EXCEPT AS PER THE SURVEYORS PLAT, ON JANUARY 8, 1885 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 29, 1885 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-21-12 ON THE RANGE LINE ON ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THIS ROAD EXTENDS NORTH ON THE RANGE LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 12-21-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 4) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE AT 50 FEET WIDE, 25 FEET ON EACH SIDE OF THE SECTION LINE, FOR 1-1/2 MILES TO THE STONE HE

FOUND AT THE EAST 1/4 CORNER OF SECTION 25-21-12; THEN CONTINUES SOUTH ON THE RANGE LINE AT 45 FEET WIDE CENTERING THE WEST LINE AT 30 FEET WEST OF THE SECTION LINE, WHICH GIVES BUT 15 FEET ON THE EAST SIDE, FOR 880 FEET; THEN CONTINUES SOUTH ON THE RANGE LINE AT 50 FEET WIDE, 30 FEET ON THE WEST SIDE AND 20 FEET ON THE EAST SIDE, FOR 1,760 FEET TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-21-12; THEN CONTINUES SOUTH ON THE RANGE LINE AT 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 36-21-12 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE TO BEGIN THIS ROAD SURVEY

- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 387 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 494 TO 496 PETITION BY JOSEPH HUMERICKHOUSE AND OTHERS FOR A ROAD IN TOWNSHIPS 21-12 AND 21-13 [PACKET 650 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 9, 1892, WAS ESTABLISHED AS 40 FOOT WIDE ROADS ON JANUARY 5, 1893 AS NOTED BY S. V. BITLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 7, 1893 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE "PROPERLY MARKED"** FOR THE SOUTHWEST CORNER OF SECTION 18-21-13 ON THE RANGE LINE ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD SURVEY EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE ROAD STONE MARKED "R" HE SET FOR THE SOUTHWEST CORNER OF SECTION 13-21-12 TO BEGIN THIS ROAD SURVEY
  - 2) THIS ROAD SURVEY EXTENDS EAST ON THE SECTION LINES TO THE ANGLE ROAD STONE HE SET AT 1,682 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 16-21-13, THEN ANGLES SOUTHEASTERLY FOR 143 FEET TO THE ANGLE ROAD STONE HE SET, THEN ANGLES NORTHEASTERLY FOR 93 FEET TO THE ROAD STONE HE SET ON THE SECTION LINE, THEN CONTINUES EAST ON THE SECTION LINES TO THE ANGLE ROAD STONE HE SET AT 1,450 FEET EAST OF THE SOUTHEAST CORNER OF SECTION 16-21-14, THEN ANGLES SOUTHEASTERLY FOR 130 FEET TO THE ANGLE ROAD STONE HE SET, THEN ANGLES NORTHEASTERLY FOR 279 FEET TO THE ANGLE ROAD STONE HE SET ON THE SECTION LINE, THEN CONTINUES EAST ON THE SECTION LINES TO THE ROAD STONE HE SET FOR THE SOUTHEAST CORNER OF SECTION 15-21-13 ON THE LYON AND COFFEY COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY
  - 3) HE NOTED THAT STONES WERE SET AND "PROPERLY" MARKED AT THE END OF EACH MILE AND ALL ANGLE POINTS ON THIS ROAD SURVEY
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-12 SHOWS AN **REA IRON PIN** AT THE "SE CORNER SECTION 13-21-12" ON THE RANGE LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 73' NW TO THE SOUTHEAST CORNER OF A WELL CURB
  - 2) 57.8' NE TO A FENCE CORNER
- 6) IN A FIELD BOOK LABELED "PRELIMINARY NOTES ROUTE NUMBER 1504" FROM THE GREENWOOD COUNTY LINE NORTH PAST ELMENDARO SCHOOL IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE, IT SHOWS A "MONUMENT" AT THE NORTHWEST CORNER OF SECTION 19-21-13 ON THE RANGE LINE, BUT DOES NOT DESCRIBE THE MONUMENT. **NOTE: THE TIES ARE THE SAME AS THE REA PIN! VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 57.8' NE TO A CORNER POST
- 2) 73.0' NW TO THE SOUTHEAST CORNER OF A WELL CURB

NORTHWEST CORNER 19-21-13