

EAST 1/4 CORNER SECTION 22, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ON PAGE 684 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 23-21-13 ON THE COUNTY LINE. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE COUNTY LINE TO THE 25" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-21-13
 - 2) 40.00 CHAINS SOUTH ON THE COUNTY LINE TO THE 26" X 15" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-21-13
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 46, A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 46 DATED JUNE 30 TO JULY 1, 1884 AT THE REQUEST OF MRS. AMY BRAUCHER AND FRED BRAUCHER TO ESTABLISH THE NORTHWEST CORNER AND TEST THE NORTHEAST CORNER OF SECTION 22-21-13 ON THE LYON AND COFFEY COUNTY LINE, APPARENTLY DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 22-21-13 ON THE LYON AND COFFEY COUNTY LINE AS HE RAN THE COUNTY LINE FROM THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-21-13 NORTH TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-21-13.
- 3) GREGORY A. MILES, L.S. 667, FOR PROJECT NUMBER 56-RS-1598-01 (3) SHOWS A **5/8" REBAR AT STATION 662+48.65** AT THE EAST 1/4 CORNER OF SECTION 22-21-13 ON THE LYON AND COFFEY COUNTY LINE.
 - 1) 32.67' EAST TO A SPIKE & WASHER IN THE TOP OF A FENCE POST
 - 2) 59.72' NE TO A SPIKE & WASHER IN A POWER POLE
 - 3) 56.35' WSW TO A SPIKE & WASHER IN A POWER POLE
- 4) THE COFFEY COUNTY HIGHWAY DEPARTMENT ON JUNE 26, 2001, SHOWS THAT **THEY FOUND A 1/2" BAR, WITH AN ADDED 1/2" EPOXY EXTENSION** AT THE WEST 1/4 CORNER OF SECTIONS 23-21-13 ON THE COFFEY AND LYON COUNTY LINE ON APRIL 28, 2000.
 - 1) AT 12.5TH AND ANGUS ROADS
 - 2) 8.5 NORTH OF A FENCE LINE TO THE EAST
 - 3) 20.0' WEST OF THE CENTERLINE OF THE ROAD NORTH-SOUTH
 - 4) 6.0' NORTH OF A FENCE LINE TO THE WEST
 - 5) 29.64' WNW TO A PK NAIL & WASHER IN A FENCE POST
 - 6) 54.69' SW TO A PK NAIL & WASHER IN A FENCE POST
 - 7) 70.2' ESE TO A 60 D NAIL & WASHER IN THE SOUTH GATE POST
- 5) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 18, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS IN COUNTY ASPHALT ROADS, **FOUND THE 1/2" EPOXY REBAR AT THE SURFACE OF THE GROUND** ON THE WEST SIDE OF LYON COUNTY ROAD "Z" AT THE EAST 1/4 CORNER OF SECTION 22 ON THE LYON AND COFFEY COUNTY LINE FROM TIES FOR LYON COUNTY PROJECT 56-RS-1598-01 (3) AND THE TIES THAT I RECEIVED FROM THE COFFEY COUNTY HIGHWAY DEPARTMENT.
 - 1) 29.7' WNW TO A FOUND PK NAIL & WASHER IN A FENCE POST
 - 2) 54.7' SW TO A FOUND PK NAIL & WASHER IN A FENCE POST
 - 3) 70.1' ESE TO A FOUND 60 D SPIKE & WASHER IN A POWER POLE
 - 4) 20.0' EAST TO THE TRAVELED WAY OF ASPHALT LYON ROAD "Z" NORTH-SOUTH [ANGUS ROAD IN COFFEY COUNTY]
 - 5) 8.5' SOUTH TO A LINE OF FENCE TO THE EAST
 - 6) 6.0' SOUTH TO A LINE OF FENCE TO THE WEST

EAST QUARTER CORNER 22-21-13