

WEST 1/4 CORNER SECTION 22, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ON PAGE 687 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 22-21-13.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 219 [PACKET 279 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY DANIEL RICH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-13 AND 21-13 THAT HE SURVEYED ON AUGUST 14 & 15, 1874, THAT WAS FILED ON FEBRUARY 5, 1875 AS A 50 FOOT WIDE ROAD EXCEPT AT THE CROSSING OF EAGLE CREEK IN SECTION 33-20-13 WHERE IT IS TO BE 60 FEET WIDE FOR 10 RODS ON EACH SIDE OF THE CENTER OF THE CHANNEL OF THE CREEK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 22-21-13 ON THIS ROAD SURVEY
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD AS SURVEYED NORTH TO THE WEST 1/4 CORNER OF SECTION 15-21-13 WAS **NOT ALLOWED** ON THIS ROAD SURVEY
 - 2) THE ROAD AS SURVEYED SOUTH TO THE SOUTHWEST CORNER OF SECTION 34-20-13 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE WAS **NOT ALLOWED** ON THIS ROAD SURVEY

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 1990, FOR JOB NUMBER 90171, SURVEY F22001 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A SURVEY TO LOCATE THE WEST LINE OF THE SOUTHWEST QUARTER OF SECTION 22-21-13 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR A BRIDGE REPLACEMENT PROJECT, SAID THAT HE EXCAVATED WITH A COUNTY BACKHOE FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 22-21-13, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 22-21-13 IN LINE WITH A LINE OF POWER POLES TO THE WEST AND ON AN EXTENSION OF AN EXISTING FENCE.
 - 1) 26.8' WEST TO A NAIL & SHINER IN A POWER POLE
 - 2) IN LINE WITH POWER POLES AND A FENCE TO THE WEST
 - 3) 2,638.8' SOUTH TO THE SOUTHWEST CORNER OF SECTION 22-21-13HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,641' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF SECTION 22-21-13
 - 2) 2,638.8' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-21-13

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 25, 2002, FOR PROJECT NUMBER 02060-02, SURVEY F22002 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A SURVEY OF THE NORTH LINE OF THE NORTHWEST QUARTER OF SECTION 22-21-13 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 02-89, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 22-21-13 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JUNE 1990. THIS SURVEY WAS FILED IN VOLUME 547 ON PAGE 593 IN THE REGISTER OF DEEDS OFFICE ON APRIL 15, 2002.
 - 1) 26.8' WEST TO A NAIL & SHINER IN A POWER POLE
 - 2) IN LINE WITH POWER POLES TO THE WEST
 - 3) IN LINE WITH A HEDGE TO THE EAST [EXTENDED]
 - 4) IN THE CENTERLINE TRAVELED WAY OF THE NORTH-SOUTH GRAVEL ROAD

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 2,638.92' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-21-13, WITH 5/8" REBARS WITH LYON COUNTY CAPS SET ON THE EAST AND WEST SIDES AND FLUSH WITH THE STONE
- 2) 2,638.86' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-21-13

WEST QUARTER CORNER 22-21-13