

**NORTH 1/4 CORNER SECTION 29, TOWNSHIP 21 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 695 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 25" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-21-13.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.23 CHAINS WEST TO THE 30" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-21-13
  - 2) 40.22 CHAINS EAST TO THE 30" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-21-13
  
- 2) GREGORY A. MILES, L.S. 667, MILES ENGINEERING, IN PLANS FOR PROJECT NUMBER 56-RS-1598 (4) SHOWS A **REBAR AT THE FENCE LINE AT P.O.T. STATION 501+05.51** AT THE NORTH 1/4 CORNER OF SECTION 29-21-13. HE APPARENTLY SET THIS ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 29-21-13. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 27.90' NORTH TO A NAIL IN A TELEPHONE POLE
  - 2) 32.50' SW TO A NAIL IN THE TOP OF A FENCE POST
  - 3) 32.00' SE TO A NAIL IN THE TOP OF A FENCE POST
  - 4) 2,661.39' WEST TO THE NORTHWEST CORNER OF SECTION 29-21-13
  - 5) 2,661.39' EAST TO THE NORTHEAST CORNER OF SECTION 29-21-13

NORTH QUARTER CORNER 29-21-13