

NORTH 1/4 CORNER SECTION 30, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ON PAGE 695 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 19" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-29-13 ON JUNE 9, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 30.84 CHAINS WEST TO THE 15" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-21-13 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 30" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-29-13

- 2) GREGORY A. MILES, L.S. 667, MILES ENGINEERING, IN PLANS FOR PROJECT NUMBER 56-RS-1598 (4) SHOWS A **REBAR AT THE FENCE LINE AT P.O.T. STATION 448+04.12** AT THE NORTH 1/4 CORNER OF SECTION 30-21-13 ON THE RANGE LINE. HE APPARENTLY SET THIS REBAR AT 2,640.00 FEET WEST OF THE NORTHEAST CORNER OF SECTION 30-29-13. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS HE DID NOT INDICATE IF HE SEARCHED FOR THE STONE OF RECORD – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 45.17' SW TO A NAIL IN A POWER POLE
 - 2) 37.77' NW TO A NAIL IN THE TOP OF A FENCE POST
 - 3) 28.46' NW TO A NAIL IN THE TOP OF A FENCE POST
 - 4) 2,640.0' WEST OF THE NORTHEAST CORNER OF SECTION 30-29-13

NORTH QUARTER CORNER 30-21-13