

SOUTHWEST CORNER SECTION 34, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ON PAGE 99 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE CORNER TO SECTIONS 33 & 34-21-13 ON THE TOWNSHIP LINE AND THE COUNTY LINE.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE TOWNSHIP LINE AND THE COUNTY LINE TO THE 23" X 10" X 3" LIMESTONE THEY SET FOR THE SOUTH 1/4 CORNER OF SECTION 34-21-13
- 2) 80.00 CHAINS EAST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 26" X 7" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 34 & 35-21-13 AT THE EAST COUNTY LINE

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 219 [PACKET 279 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY DANIEL RICH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-13 AND 21-13 THAT HE SURVEYED ON AUGUST 14 & 15, 1874, THAT WAS FILED ON FEBRUARY 5, 1875 AS A 50 FOOT WIDE ROAD EXCEPT AT THE CROSSING OF EAGLE CREEK IN SECTION 33-20-13 WHERE IT IS TO BE 60 FEET WIDE FOR 10 RODS ON EACH SIDE OF THE CENTER OF THE CHANNEL OF THE CREEK, SAID THAT **HE FOUND THE STONE** AT THE CORNER TO SECTIONS 33 & 34-21-13 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD AS SURVEYED NORTH TO THE WEST 1/4 CORNER OF SECTION 15-21-13 WAS NOT ALLOWED ON THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 73 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 294 TO 296 PETITIONED BY JAMES A. McCULLOCH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-13 [PACKET 321 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 19, 1880, WAS ESTABLISHED AT A 60 FOOT WIDE ROAD* ON JULY 113, 1880, AND WAS RECORDED N JULY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-20-13 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE TO COMMENCE THIS ROAD SURVEY. *A NOTE IN PACKET 321 STATES: ORDERED BY THE BOARD – THAT AS TO THE ROAD LOCATED ON THE EAST LINE OF SECTION NO. 21, T 21, R 13 IN LYON COUNTY, KANSAS – THAT THE SAME BE CONFIRMED AT THE WIDTH OF THIRTY-THREE FEET ALONG THE EAST LINE OF SAID SECTION – THE SECTION LINE TO BE AND CONSTRUED THE MIDDLE OF THE SAID ROAD, AND THAT THE BALANCE OF SAID ROAD BE AND IS HEREBY CONFIRMED ACCORDING TO THE REPORT OF SAID VIEWERS. I. A. TAYLOR, CHAIRMAN, BOARD OF COUNTY COMMISSIONERS HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 3-1/2 MILES TO THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 15-21-13 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 183 DATED MARCH 27, 1880, FOR A COUNTY ROAD IN TOWNSHIP 21-13, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-21-13 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 15-21-13 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 70 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 282 TO 284 PETITIONED BY JACOB. W. ELLIS AND OTHERS FOR A COUNTY ROAD ON THE GREENWOOD COUNTY LINE IN TOWNSHIPS 21-12 AND 21-13 [PACKET 319 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 17, 1880, WAS ESTABLISHED AS A 40 FOOT AND 50 FOOT WIDE ACCORDING TO THE SURVEY PLAT ON JULY 13, 1880, AND WAS RECORDED ON JULY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-21-13 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE ON THIS ROAD SURVEY.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS 50 FOOT WIDE ROAD EXTENDS WEST ON THE TOWNSHIP LINE AND THE COUNTY LINE FOR 1 MILE AND 60 RODS; THEN CONTINUES WEST ON THE TOWNSHIP LINE AND THE COUNTY LINE AS A 40 FOOT WIDE ROAD TO THE RANGE LINE BETWEEN RANGES 12 & 13; THEN CONTINUES WEST ON THE TOWNSHIP LINE AND THE COUNTY LINE AS A 50 FOOT WIDE ROAD FOR 3 MILES TO THE CORNER TO SECTIONS 3, 4, 33 & 34 IN TOWNSHIPS 21 & 22 OF RANGE 12 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS 50 FOOT WIDE ROAD EXTENDS EAST ON THE TOWNSHIP LINE AND THE COUNTY LINE FOR 1 MILE TO THE CORNER TO SECTIONS 34 & 35-21-13 TO COMMENCE THIS ROAD SURVEY
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 27, 1992 FOR PROJECT NUMBER 92038-02, SURVEY F26001 IN THE SURVEY FILE FOR TOWNSHIP 21-13 TO LOCATE THE GOVERNMENT CORNERS ON THE LYON/COFFEY COUNTY LINE COMMON TO SECTIONS 26, 27, 34 & 35 IN 21-13, SAID THAT HE DUG WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTHWEST CORNER OF SECTION 34-21-13 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE. **HE FOUND THE GLO STONE AT A DEPTH OF 20"** AT THE SOUTHWEST CORNER OF SECTION 34-21-13. HE SAID THAT THIS LIMESTONE WAS FIRM IN THE BROWN CLAY AND IS OF THE TYPE NORMALLY FOUND FOR GLO STONES, I.E. HARD AND TAN ON THE OUTSIDE AND GRAY/WHITE ON THE INSIDE, WELL FORMED AND HEAVILY FOSSILIZED, AND THE STONE IS ALSO THE DIMENSIONS INDICATED BY THE NOTES. **HE SET A 1/2" REBAR ON THE SOUTH SIDE OF THE STONE AND A 1/2" REBAR ON THE NORTH SIDE OF THE STONE BENT OVER THE TOP OF THE STONE.**
- 1) 35.1' SE TO A CONCRETE NAIL & SHINER IN A POWER POLE
 - 2) 39.0' NE TO A CONCRETE NAIL & SHINER IN A POWER POLE
 - 3) 54.5' SSW TO THE TOP OF A TELEPHONE PEDESTAL
 - 4) IN THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD EAST-WEST
 - 5) IN THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD TO THE SOUTH
 - 6) 2.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD TO THE NORTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,649.79' EAST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 34-21-13
 - 2) 5,299.17' EAST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 34-21-13, AT THE TOWNSHIP CORNER ON THE LYON, COFFEY AND GREENWOOD COUNTY LINE

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 10,598.32' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE
SOUTHEAST CORNER OF SECTION 35-21-13 IN COFFEY COUNTY

SOUTHWEST CORNER 34-21-13